

## ADMA-Slim v35

*Mini GNSS/inertial system: If size and weight matters*

The new full-fledged ADMA-Slim GNSS/inertial system has been specially developed for applications with space or weight restrictions. It is smaller, lighter and more compact, without limitations in functionality or quality of measurement data. ADMA-Slim is the perfect choice for applications in motorcycles, overrunnable platforms for GSTs (Guided Soft Targets) or VRUs (Vulnerable Road Users such as pedestrians or cyclists), for example.

ADMA-Slim is based on the proven ADMA technology for centimeter accuracy in positional data acquisition. It delivers precise, smooth and consistent signals even when GNSS reception is poor.



<b>0.01 m</b>	<b>0.04 km/h</b>	<b>0.05 °</b>	<b>0.02 °</b>	<b>&lt; 1 ms</b>	<b>1 kHz</b>
Position accuracy ( $1\sigma$ ) <sup>2</sup>	Velocity accuracy (RMS) <sup>3</sup>	Heading accuracy ( $1\sigma$ ) <sup>2</sup>	Roll/Pitch accuracy ( $1\sigma$ ) <sup>2</sup>	Data latency	Data output rate

## APPLICATIONS

The ADMA-Slim is a state-of-the-art device designed for precise data measurement in various applications. With its advanced strap-down technology, it guarantees stability and resistance to unwanted vibrations, ensuring accurate and reliable results.

One of the key advantages of the ADMA is its excellent suitability for installation on overrunnable platforms. Unlike many other inertial devices, the ADMA does not require a lengthy initialization process. The stability of the Kalman filter guarantees reliable results without the need for reinitialization even after an overrun of the platform.

Additionally, the ADMA system is also suitable for all other testing applications, such as VD (vehicle dynamics) or ADAS (Advanced Driver Assistance Systems) testing. Its robust design and stable performance make it a versatile tool for various testing scenarios.


## ADMA ADD-ONS AND OPTIONS

**Meet new measurement and testing requirements with Add-Ons and Options.**


The new generation of ADMA 3.5 devices now allows our customers to meet their new and changing needs. Our focus is on straight-forward use and increased productivity. The Add-Ons and Options can be activated quickly and conveniently by entering a license key. This is possible at any time without modifications to the hardware. A high degree of flexibility is thus ensured.




**Add-On DELTA 1:5**  
Relative data calculation via WiFi in real-time for multi-vehicle operation




**Add-On Smoothing**  
Define maximum step size for the GNSS signal



**Add-On LATDEV**  
Real-time calculation of the lateral deviation



**Add-On PTP**  
Time synchronization with generalized Precision Time Protocol (gPTP)



**Add-On FILTER**  
Option for online signal filtering



**Add-On BRAKING**  
Real-time calculation of brake performance data according to international regulations



### Option RTK2

High-precision position measurement using correction data



### Option Multi-GNSS

Multi-GNSS: Use of multiple satellite systems such as GPS, GLONASS, Galileo, BeiDou



### Option Dual-Ant

Two GNSS antenna option



### Option DGNSS Correction Data

Correction data reception via Ethernet



### Option GNSS-Raw Data

Raw data output via Ethernet for post-processing




### Option 1kHz

Data output rate of 1 kHz via CAN or Ethernet interface




### Option Multi-CAN

Data output via several CAN channels simultaneously



### Option Vehicle Model

2D vehicle model predicts vehicle behavior, supports IMU & adapts to conditions



### Option Internal Memory

Storing ADMA measurement data in internal memory

## TECHNICAL DATA

<b>Complete system*1</b>	
GNSS constellations	GPS L1, L2 GLONASS L1, L2 BeiDou*4 B1, B2 Galileo*4 E1, E5
Dual antenna	Optional
Position accuracy (1 $\sigma$ )*2	0.01 / 0.20 / 0.60 / 1.20 / 1.50 m
Angle Measurement range roll / pitch / yaw	60 ° / 60 ° / $\pm 180$ °
Angle Measurement accuracy roll & pitch (1 $\sigma$ ) / yaw (1 $\sigma$ ) / sideslip (RMS)	0.02 / 0.05 / 0.15 °
Angle resolution	0.005 °
Velocity accuracy (RMS)*3	0.04 km/h
Position error after 10 / 30 / 60 sec GNSS outage (RMS)*3	0.4 / 5.0 / 40.0 m
Velocity error after 10 / 30 / 60 sec GNSS outage (RMS)*3	0.06 / 0.5 / 1.5 m/sec
Roll / Pitch angle error after 10 / 30 / 60 sec GNSS outage (RMS)*3	0.05 / 0.15 / 0.30 °
Heading angle error after 10 / 30 / 60 sec GNSS outage (RMS)*3	0.05 / 0.15 / 0.30 °
Data output rate	50 / 100 / 200 / 250 / 500 Hz / (1000 Hz)*4
Calculation latency	1 msec

---

**Sensors - Gyros**

Sensor Technology	3 MEMS gyros
Measurement range	$\pm 450$ °/s
Data output resolution	0.0001 °/s
Bias repeatability typ. ( $1\sigma$ )	0.2 °/s
In-run-bias typ.	6 °/h
Noise (random walk) typ.	0.3 °/ $\sqrt{h}$
Scale factor	0.2 %
Sensor bandwidth	330 Hz

---

**Sensors - Accelerometers**

Sensor Technology	3 MEMS accelerometers
Measurement range	$\pm 5$ g / ( $\pm 15$ g)*4
Data output Resolution	0.0001 g
Bias repeatability typ.	4 mg
In-run-bias typ. ( $1\sigma$ )	32 $\mu$ g
Noise (random walk) typ.	50 $\mu$ g / $\sqrt{Hz}$
Scale factor ( $1\sigma$ )	0.2%
Sensor bandwidth	330 Hz

---

**Interfaces**


---

Ethernet	1x 1 Gbit Data input/output, configuration and firmware update, driving robot data output, optional for relative data calculation and DGNSS routing.
CAN	1x CAN 2b, 1 Mbit Data output, input*4
Serial	1x RS232 GNSS Receiver; DGNSS correction data input 1x RS232 GNSS Receiver; GPGGA Log output, IPS (Indoor Positioning System)
Digital/Analog Input	up to 4x Digital / Analog (16 bit) e.g. Frequency, Brake trigger, ...
Digital Output	up to 4x Digital TTL e.g. PPS, Frequency, PPD Pulse per distance, ...
Connector type	Lemo; SC; Samtec
GNSS	2x SMA GNSS Antenna connectors

---

**Hardware / Miscellaneous**


---

Ordering Variants	Lemo, SC, OEM
Internal Memory	up to 64 GB
Power supply	9 to 32 VDC typ. 15 W
Dimensions (W x L x H)	Lemo version 130 x 186 x 47 mm SC version 130 x 194 x 47 mm OEM version 125 x 148 x 31 mm
Weight	1.5 kg
Operating temperature	-20 to +60 °C

\*1 Open sky conditions.

\*2 With RTK2 corrections at <10 km from the GNSS Base Station

\*3 Typical values according to internal test standards with settled Kalman filter.

\*4 Optional

\*5 Depending on GNSS correction data and license model

**For any further questions:** [support@genesys-offenburg.de](mailto:support@genesys-offenburg.de)